

Product Specifications

Item #GPD730



**Magid® D-ROC® Lightweight NitriX® Grip
Technology Sandy Nitrile Palm Coated Work Glove
– Cut Level 2**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; full flat nitrile undercoat; three-quarter NitriX® Grip Technology overcoat
Color(s)	Salt & pepper shell; matte black three-quarter coat over glossy black full coat
Size(s)	5 – 10
Cuff/Finish	Color-coded overcast: grey (5), blue (6), green (7), red (8), black (9), orange (10)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• Hyperon® shell feels cool on the skin and delivers dependable cut resistance • Unique, double-dip coating adds an extra layer of protection • Full nitrile undercoat protects against liquids, oils and solvents • Three-quarter NitriX® Grip Technology sandy nitrile overcoat ensures a solid, secure grip in wet or dry applications • Dark color hides dirt and grime to extend wear • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • PPG Tested • ANSI Level 2 Cut Resistance and ANSI Level 6 Abrasion Resistance	

APPLICATIONS	
Assembly, machining, automotive manufacturing, metal handling and maintenance	

AVAILABLE STYLES						
Size	5	6	7	8	9	10
Part Number	GPD7305	GPD7306	GPD7307	GPD7308	GPD7309	GPD73010

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
EN 388:2003 Puncture Resistance	6.4	4

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

Test Method	Clause	EN Level
Cut Resistance	6.2	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Efi Vrshek	Date	02/14/2013	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 4

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.