

# Product Specifications

Style #GPD748



## D-ROC®

Magid® D-ROC® GPD748 Hyperon® 13-gauge TriTek Palm® Coated Work Glove – Cut Level A7

### PRODUCT DESCRIPTION

<b>Product Classification</b>	Special Purpose Work Glove – Cut Resistant, Coated
<b>Construction/Design</b>	13-gauge, seamless machine knit
<b>Composition</b>	Hyperon® shell; TriTek Palm® coating
<b>Color(s)</b>	Hi-viz yellow shell; black palm coating
<b>Size(s)</b>	6 – 12
<b>Cuff/Finish</b>	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
<b>Unit of Measure</b>	Pair (must be ordered in multiples of 12 pairs)
<b>Packaging</b>	12 pairs per inner pack, 144 pairs per case

### FEATURES & BENEFITS

- 13-gauge Hyperon® shell delivers breathability, comfort, and cut protection
- TriTek Palm® coating strengthens grip and minimizes saturation in heavy liquid and oil applications
- Resilient TriTek palm coating provides over 2X the abrasion resistance of other coatings for unbeatable durability while maintaining extreme dexterity
- Touchscreen compatible to maintain user safety while operating electronic devices
- Nitrile reinforced thumb saddle enhances durability at a critical wear point
- High-visibility shell color enhances worker protection and ensures worker compliance
- Shield graphic is color-coded by cut level to easily identify cut protection from a distance
- ANSI Level A7 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Level 3 Puncture Resistance

### APPLICATIONS

Assembly or movement of large, bulky, or heavy objects with sharp edges, Automotive Manufacturing, Metal Fabrication, Appliance Manufacturing, Aerospace Manufacturing, and Glass Fabrication.

AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Item Number	GPD7486	GPD7487	GPD7488	GPD7489	GPD74810	GPD74811	GPD74812
FUNCTIONAL PERFORMANCE							
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria							
Test Method				Clause	ANSI Level		
ASTM F2992-15 Cut Resistance				-	A7		
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)				-	4		
ANSI/ISEA: 105-2011 Puncture Resistance (other than hypodermic needle)				6.4	3		
SERVICE LIFE							
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.							
Critical Defects	Holes/tears						
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects						
LAUNDERING GUIDELINES							
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.							
GENERAL INFORMATION							
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.							

<b>Originator</b>	Scott Daigle	<b>Date</b>	12/6/2019		
<b>Revised By</b>	Brittany Cohen	<b>Date</b>	1/27/2020	<b>Revision #</b>	1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD