

Product Specifications

Style #GPD765



D-ROC®
by Magid

**Magid® D-ROC® 13-Gauge Hi-Viz Crinkle Latex
Coated Work Glove-Cut Level A8**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; crinkle latex palm coating
Color(s)	Salt & pepper shell; blue palm coating
Size(s)	5-12
Cuff/Finish	Color-coded overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)

FEATURES & BENEFITS	
• 13-Gauge Hyperon® shell delivers breathability, comfort, and cut protection • Crinkle Latex palm coating provides superior wet and dry grip with good tactile sensitivity in heavy-duty conditions • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Machine washable for longer service life • PPG Tested • ANSI Level A8 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Puncture Level 5 Resistance	

APPLICATIONS	
Appliance and automotive manufacturing, glass handling, metal handling, metal stamping, metal fabrication, and construction	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD7655	GPD7656	GPD7657	GPD7658	GPD7659	GPD76510	GPD76511	GPD76512

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A8
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
ANSI/ISEA: 105-2011 Puncture Resistance (other than hypodermic needle)	6.4	5
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.		
CAUTION – Contains natural rubber latex which may cause allergic reactions in some individuals		

Originator	Scott Daigle	Date	6/7/2019	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.