

Product Specifications

Item #GPD778



D-ROC®

Magid® D-ROC® GPD778 Lightweight Hyperon™ Foam Nitrile Palm Coated Work Gloves – Cut Level A7

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon™ and steel blended shell; foam nitrile palm coating
Color(s)	Grey shell; black palm coating
Size(s)	5-12
Cuff/Finish	Knit-wrist cuff with color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• Lightweight, 13-gauge Hyperon™ and steel blended shell delivers a ground-breaking combination of lightweight comfort and extreme 360° cut protection • Touchscreen compatible to maintain user safety while operating electronic devices • Soft, flexible foam nitrile palm coating ensures superb grip while channeling away oils and liquids • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Cut Level A7 cut resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 4 Puncture Resistance	

APPLICATIONS	
Automotive manufacturing, metal fabrication, household appliance assembly, aerospace manufacturing, and glass fabrication	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GPD7785	GPD7786	GPD7787	GPD7788	GPD7789	GPD77810	GPD77811	GPD77812

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A7
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.		

Originator	Scott Daigle	Date	12/8/2017	
Revised By	Kim Schultz	Date	11/09/2023	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

