

Product Specifications

Item #GPD780RT



D-ROC®
by Magid

**Magid® D-ROC® NitriX® Palm Coated Work Glove
with Reinforced Thumb Saddle – Cut Level A4**

PRODUCT DESCRIPTION							
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated						
Construction/Design	10-gauge, seamless machine knit, reinforced thumb saddle						
Composition	Hyperon® shell; NitriX® Grip Technology palm coating; nitrile reinforced thumb saddle						
Color(s)	Salt & pepper shell; black palm coating; green nitrile reinforcement on thumb saddle						
Size(s)	6 – 12						
Cuff/Finish	Color-coded elasticized overcast: white (6), green (7), brown (8), yellow (9), black (10), grey (11), blue (12)						
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)						
Packaging	12 pairs per inner pack, 12 inner packs per case						
FEATURES & BENEFITS							
• Durable 10 gauge Hyperon® shell delivers breathability, comfort and 360° cut protection • NitriX Grip Technology palm coating delivers rock-solid grip in oily applications • Green nitrile-reinforced thumb saddle coating delivers up to 1.7 times the abrasion resistance at critical wear point • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • PPG Tested • ANSI Level A4 Cut Resistance, ANSI level 4 Abrasion Resistance, and ANSI Level 4 Puncture Resistance							
APPLICATIONS							
Assembly, machining, automotive manufacturing, metal handling, metal fabrication, maintenance and construction							
AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Item Number	GPD780RT6	GPD780RT7	GPD780RT8	GPD780RT9	GPD780RT10	GPD780RT11	GPD780RT12

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A4
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
-------------------------	-------------

Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects
----------------------	---

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	4/27/2017	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.