

Product Specifications

Item #GPD790HV



D-ROC[®]
by Magid

**Magid[®] D-ROC[®] GPD790HV Hi-Vis Foam
Nitrile Palm Coated Work Glove – Cut Level
A5**

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon [®] and steel blended shell; foam nitrile palm coating
Color(s)	Hi-vis yellow shell; hi-vis orange palm coating
Size(s)	6 - 12
Cuff/Finish	Color-coded overcast: black (6), white (7), green (8), brown (9), yellow (10), grey (11), red (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS

- Hyperon[®] and steel shell delivers comfort, dexterity, and ANSI Level A5 cut protection
- Durable 13-gauge, Hyperon[®] shell delivers breathability, comfort, and cut protection
- Soft, flexible foam nitrile palm coating ensures superb grip while channeling away oils and liquids
- Hi-vis yellow and hi-vis orange color combination enhances visibility and encourages worker compliance
- Color-coded overcast reduces fraying and acts as a visual aid for sizing
- Machine washable for longer service life
- PPG and NEAT Tested
- ANSI Level A5 Cut Resistance, ANSI Level 5 Abrasion Resistance and ANSI Level 3 Puncture Resistance

APPLICATIONS

Metal stamping, metal fabrication, metal handling, automotive manufacturing, glass fabrication and paper production

AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Part Number	GPD790HV6	GPD790HV7	GPD790HV8	GPD790HV9	GPD790HV10	GPD790HV11	GPD790HV12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	5
EN 388:2003 Puncture Resistance	6.4	3

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	5

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Efi Vrshek	Date	3/15/2013	
Revised By	Kim Schultz	Date	11/09/2023	Revision # 9

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.