

Product Specifications

Item #GPD795



D-ROC®

Magid® D-ROC® Hyperon® 13-Gauge Hi-Vis Double-Dipped Three-Quarter Nitrile® Grip Technology Coated Work Glove – Cut Level A7

PRODUCT DESCRIPTION							
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated						
Construction/Design	13-gauge, seamless machine knit shell; three-quarter double-dipped coating						
Composition	Hyperon® shell; NitriX® Grip Technology coating						
Color(s)	Hi-vis lime yellow shell; black three-quarter coating						
Size(s)	6-12						
Cuff/Finish	Knit-wrist cuff with color-coded elasticized overcast: grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)						
Unit of Measure	Pair (12 pair minimum order increment)						
Packaging	12 pairs per inner pack, 120 pairs per case						
FEATURES & BENEFITS							
• 13-gauge Hyperon® shell is cool and lightweight for incredible comfort and cut protection • Three-quarter double dipped NitriX® Grip Technology Palm Coating delivers rock-solid grip in oily applications, enhanced abrasion resistance and increased wear life • Touchscreen compatible • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • PPG Tested • ANSI Level A7 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Level 4 Puncture Resistance							
APPLICATIONS							
Automotive manufacturing, metal fabrication, household appliance assembly, aerospace manufacturing, and glass fabrication							
AVAILABLE STYLES							
Size	6	7	8	9	10	11	12

Part Number	GPD7956	GPD7957	GPD7958	GPD7959	GPD79510	GPD79511	GPD79512
--------------------	---------	---------	---------	---------	----------	----------	----------

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A7
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	4

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	4/10/2020	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 2

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD

1300 Naperville Drive | Romeoville, IL 60446
800-444-8030 | magidglove.com