

Product Specifications

Style #GPD800



D-ROC®
by Magid

**Magid® D-ROC® GPD800 Lightweight Polyurethane
Palm Coated Work Glove – Cut Level A6**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® and steel shell with polyurethane palm coating
Color(s)	Dark grey shell; grey palm coating
Size(s)	5 – 11
Cuff/Finish	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS	
• 13-gauge machine Hyperon® blended shell delivers a ground-breaking combination of ultra lightweight comfort and maximum cut protection • Polyurethane palm coating maintains dexterity while delivering excellent grip • Touchscreen compatible • Dark grey color hides dirt and grime to extend wear • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • Machine washable for longer service life • NEAT Tested • ANSI Cut Level A6 protection, ANSI Level 6 Abrasion Resistance and ANSI Level 4 Puncture Resistance	

APPLICATIONS	
Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.	

AVAILABLE STYLES							
Size	5	6	7	8	9	10	11
Part Number	GPD8005	GPD8006	GPD8007	GPD8008	GPD8009	GPD80010	GPD80011

FUNCTIONAL PERFORMANCE**US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria**

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A6
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	6
EN 388:2003 Puncture Resistance	6.4	4

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistance	-	5

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

Test Method	Clause	EN Level
Blade Cut Resistance	6.2	5

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Sarah Anderson	Date	06/24/2016	
Revised By	Dana Cornish	Date	05/16/2022	Revision # 6

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.