

Product Specifications

Style #GPD803



D-ROC®
by Magid

**Magid® D-ROC® Extended Cuff Lightweight Coated
Work Glove – Cut Level A6**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit; 3” cuff
Composition	Hyperon™ and steel blended shell with steel; polyurethane palm coating
Color(s)	Dark grey shell; grey palm coating
Size(s)	6 – 11
Cuff/Finish	Color-coded elasticized overcast: grey (6), light blue (7), green (8), red (9), black (10), orange (11)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case
FEATURES & BENEFITS	
• ANSI Cut Level A6 Resistance, ANSI Level 6 Abrasion Resistance and ANSI Level 4 Puncture Resistance • 13-gauge machine knit Hyperon™ and steel blended shell delivers a ground-breaking combination of ultra lightweight comfort and maximum cut protection • 3” extended cuff design provides additional forearm protection from laceration hazards • Polyurethane palm coating maintains dexterity while delivering excellent grip • Touchscreen compatible • Dark grey shell color hides dirt to extend worker wear time • Color-coded overcast acts as a visual aid for sizing and helps prevent fraying • PPG Tested • Machine washable for longer service life	

APPLICATIONS						
Appliance and automotive manufacturing, glass handling, metal handling, metal fabrication and metal stamping.						
AVAILABLE STYLES						
Size	6	7	8	9	10	11
Part Number	GPD8036	GPD8037	GPD8038	GPD8039	GPD80310	GPD80311
FUNCTIONAL PERFORMANCE						
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria						
Test Method				Clause	ANSI Level	
ASTM F2992 Cut Resistant				-	A6	
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)				-	6	
EN 388:2003 Puncture Resistance				6.4	4	
European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks						
Test Method				Clause	EN Level	
Blade Cut Resistance				6.2	5	
SERVICE LIFE						
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.						
Critical Defects	Holes/tears					
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects					
LAUNDERING GUIDELINES						
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.						
GENERAL INFORMATION						
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.						

Originator	Sarah Anderson	Date	06/24/2016			
Revised By	Dana Cornish	Date	06/01/2022	Revision #	6	

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.