

Product Specifications

Item #GPD824



D-ROC®

**Magid® D-ROC® Ultra-Lightweight Polyurethane
Palm Coated Work Gloves – Cut Level A5**

For jobs that involve handling sharp materials, the GPD824 ultra-lightweight 18-gauge Aramid work gloves deliver ANSI A5 cut protection plus extreme dexterity for picking up even the smallest objects.

PRODUCT DESCRIPTION								
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated							
Construction/Design	18-gauge, seamless machine knit							
Composition	Aramid blended shell; polyurethane palm coating							
Color(s)	Teal shell; black palm coating							
Size(s)	5-12							
Cuff/Finish	Knit-wrist cuff with color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)							
Unit of Measure	Pair							
Packaging	12 pairs per inner pack, 144 pairs per case							
FEATURES & BENEFITS								
• Ultra-lightweight 18-gauge Aramid shell delivers excellent dexterity and comfort plus 360° cut protection • Aramid blended shell is inherently heat and flame resistant plus a small percentage of elastic/spandex improves comfort • Polyurethane palm coating maintains dexterity while delivering an excellent grip • Touchscreen compatible • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • PPG Tested • ANSI Level A5 Cut Resistance, ANSI Level 3 Abrasion Resistance and ANSI Level 2 Puncture Resistance								
APPLICATIONS								
Assembly, machine, automotive manufacturing, metal handling, maintenance and construction								
AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Part Number	GPD8245	GPD8246	GPD8247	GPD8248	GPD8249	GPD82410	GPD82411	GPD82412

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	3
EN 388:2003 Puncture Resistance	6.4	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects Holes/tears

Major Defects Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut or puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	12/8/2017	
Revised By	Kim Schultz	Date	05/20/2026	Revision # 3

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.