

Product Specifications

Item #GPD887H



D-ROC®

Magid® D-ROC® AeroDex® 13-Gauge RepTek Grip® Silicone Palm Coated Work Glove with Acrylic Liner – Cut Level A8

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	AeroDex® shell; RepTek Grip® Silicone palm coating, acrylic liner
Color(s)	Blue shell; clear palm coating
Size(s)	5-12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
• 13-gauge AeroDex® engineered shell delivers A8 cut resistance • Durable clear silicone palm coating provides unmatched dry grip even on heavy objects • Silicone coating delivers adhesion resistance, preventing sealant and hot melt build up • Acrylic liner offers additional cut protection and heat resistance allowing the glove to reach ANSI Contact Heat Level 5 - 320°C (606°F) • Shield graphic is color-coded by cut level to easily identify cut protection from a distance • Color-coded overcast acts as a visual aid for sizing and reduces fraying • Machine washable for longer service life • ANSI Level A8 Cut Resistance, ANSI Level 6 Abrasion Resistance, ANSI Level 3 Puncture Resistance	

APPLICATIONS

Appliance manufacturing, automotive, construction, glass handling, machining, metal handling, metal stamping, maintenance, and assembly. Ideal for applications that require the manipulation of small parts or tactile sensitivity.

	AVAILABLE STYLES							
Size	5	6	7	8	9	10	11	12
Item Number	GPD887H5	GPD887H6	GPD887H7	GPD887H8	GPD887H9	GPD887H10	GPD887H11	GPD887H12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A8
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	6
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	3
ANSI/ISEA: 105-2016 Conductive Heat Resistance	-	5

SERVICE LIFE	
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.	
Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Dana Cornish	Date	08/11/2022	
Revised By	Kim Schultz	Date	02/20/2023	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.