

Product Specifications

Style #GPD954W



D-ROC®

Magid® D-ROC® Hyperon 10-Gauge Sandy Latex Coated Work Glove with Insulcore® Fleece liner – Cut Level A9

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut-Resistant, Coated, Lined
Construction/Design	10-gauge, seamless machine knit
Composition	Hyperon® shell; Sandy latex palm coating; Acrylic fleece liner
Color(s)	Gray shell; black palm coating
Size(s)	7 – 12
Cuff/Finish	Color-coded elasticized overcast: light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 72 pairs per case

FEATURES & BENEFITS	
• 10-gauge Hyperon® shell • Sandy latex palm coating maintains dexterity while delivering excellent grip on wet, oily, and dry applications • Insulcore® brushed acrylic fleece liner adds warmth and comfort • Touchscreen compatible to maintain user safety while operating electronic devices • Nitrile reinforced thumb saddle enhances durability at a critical wear point • Machine washable for longer service life • ANSI Level A9 Cut Resistance, ANSI Level 2 Abrasion Resistance, ANSI Level 3 Puncture Resistance	

APPLICATIONS	
Construction, waste removal, transportation, and cold storage applications.	

AVAILABLE STYLES								
Size	5	6	7	8	9	10	11	12
Item Number	GPD954W5	GPD954W6	GPD954W7	GPD954W8	GPD954W9	GPD954W10	GPD954W11	GPD954W12

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A9
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	2
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	3
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.		

Originator	Kim Schultz	Date	10/13/2025		
Revised By	Kim Schultz	Date	11/10/2025	Revision #	1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.