

Product Specifications

Style #GPD985



D-ROC®
by Magid

Magid® D-ROC® 13-Gauge Hi-Vis Non-Marring Crinkle Latex Coated Cut Resistant Work Glove - Cut Level A9

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	Hyperon® shell; non-marring crinkle latex palm coating
Color(s)	Hi-vis yellow shell; black palm coating
Size(s)	5-12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
<ul style="list-style-type: none">• 13-Gauge Hyperon® shell delivers breathability, comfort, cut protection• Non-marring crinkle latex coating is 2 times more durable than traditional latex• Soft and flexible coating reduces hand fatigue without sacrificing grip or durability• Nitrile reinforced thumb saddle enhances durability at a critical wear point• Color-coded overcast acts as a visual aid for sizing and helps prevent fraying• High-visibility color enhances worker protection in low-light conditions and ensures worker compliance• Shield graphic is color-coded by cut level to easily identify cut protection from a distance• Machine washable for longer service life• NEAT tested• ANSI Level A9 Cut Resistance, ANSI Level 4 Abrasion Resistance, ANSI Puncture Level 5 Resistance	

APPLICATIONS

Appliance Manufacturing, Automotive, Construction, Glass Handling, Machining, Metal Handling, Metal Stamping, Paper Production

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	GPD9855	GPD9856	GPD9857	GPD9858	GPD9859	GPD98510	GPD98511	GPD98512

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A9
ASTM D3389-10 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
EN 388:2003 Puncture Resistance	6.4	5

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Scott Daigle	Date	12/16/2022	
Revised By	Kim Schultz	Date	04/03/2024	Revision # 4

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD