

Product Specifications

Item #HV250W



D-ROC®
by Magid

Magid® ROC® HV250W Waterproof Thermal Coated Work Glove – Cut Level A2

For jobs that require handling sharp materials in cold and wet conditions, the Magid® ROC® HV250W Waterproof Thermal Coated Work Glove keeps hands dry and warm while also delivering ANSI level A2 cut protection.

PRODUCT DESCRIPTION

| | |
|-------------------------------|--|
| Product Classification | General Purpose Work Glove – Coated |
| Construction/Design | 13-gauge, insulated seamless machine knit shell |
| Composition | 100% polyester with acrylic fleece liner; waterproof membrane; NitriX® Grip Technology coating |
| Color(s) | Hi-viz orange shell; black palm coating |
| Size(s) | 7 – 11 |
| Cuff/Finish | Color-coded elasticized overcast: green (7), brown (8), yellow (9), black (10), grey (11) |
| Unit of Measure | PR |
| Packaging | 12 pairs per inner pack, 12 inner packs per case |

FEATURES & BENEFITS

- Insulcore™ Extreme Thermal Lining delivers ultimate protection against cold temperatures
- Aquagard™ Waterproof Membrane is guaranteed to keep hands dry
- NitriX® Grip Technology palm coating delivers rock-solid grip, enhanced abrasion resistance and increases wear life
- High-visibility color enhances worker protection and compliance
- Color-coded overcast reduces fraying and acts as a visual aid in sizing
- Machine washable for longer service life
- 360° ANSI Level A2 Cut Resistance, ANSI Level 4 Abrasion Resistance and ANSI Level 3 Puncture

APPLICATIONS

Construction, waste removal, transportation and cold storage applications.

AVAILABLE STYLES

| Size | 7 | 8 | 9 | 10 | 11 |
|--------------------|---------|---------|---------|----------|----------|
| Item Number | HV250W7 | HV250W8 | HV250W9 | HV250W10 | HV250W11 |

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

| Test Method | Clause | ANSI Level |
|--|--------|------------|
| ASTM F2992 Cut Resistance | - | A2 |
| ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load) | - | 4 |
| EN 388:2003 Puncture Resistance | 6.4 | 3 |

US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

| Test Method | Clause | ANSI Level |
|------------------------------|--------|------------|
| ASTM F-1790-97 Cut Resistant | - | 2 |

European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks

| Test Method | Clause | EN Level |
|----------------------|--------|----------|
| Blade Cut Resistance | 6.2 | 3 |

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

| | |
|-------------------------|---|
| Critical Defects | Holes/tears |
| Major Defects | Dimensional or weight nonconformance, discoloration, other fabric defects |

LAUNDERING GUIDELINES

Machine wash in warm water (not to exceed 104° F or 40° C) using a mild commercial soap or detergent. Rinse in cold water and air dry or tumble dry with a low temperature setting (not to exceed 104° F or 40° C).

| | | | | |
|-------------------|----------------|-------------|------------|---------------------|
| Originator | Sarah Anderson | Date | 08/04/2016 | |
| Revised By | Brittany Cohen | Date | 07/11/2017 | Revision # 2 |

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD