

DURAFLEX PYTHON® HARNESSES

TECHNICAL DATA
SP156 Rev. D
Apr. 2024

MODELS: PYTHON P950 SERIES

The DuraFlex Python® Harness features cushioned tubular webbing in the shoulder straps to minimize possible discomfort around the neck and shoulders, and stretchable DuraFlex webbing in the lower torso, providing greater flexibility, mobility and less fatigue.

MATERIALS

Webbing (DuraFlex):	Polyester, Urethane Elastomer
Elastic Keepers:	Polyester, Nylon, Lycra
Thread:	6 cord bonded 3 strand polyester thread. Minimum tensile of 42 lb
D-ring:	Clear Chromate Finished Carbon Steel
Hardware:	Steel
Labels:	Valeron
Label Pack:	Evoprene, Nylon

TECHNICAL

Min. Working Load:	420 lb (181 kg)
Webbing Min. Tensile:	5,000 lb (22kN)
D-ring Min. Tensile:	5,000 lb (22kN)
Buckle Min. Tensile:	4,000 lb (18kN)

CERTIFICATION

Meets OSHA 1910.66, 1926.502, ANSI Z359.1 and CSA requirements.



P950/UGN shown. Also available in blue webbing.

SKU	SIDE D-RINGS	CHEST STRAP	SHOULDER STRAP	LEG STRAPS	WEIGHT	SPECIAL FEATURES
P950/UGN	No	Mating	Friction	Mating	3.2 lb (1.4kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-4/UGN	No	Mating	Friction	Tongue	3.2 lb (1.5 kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-58/UGN	Yes	Mating	Friction	Tongue	4.4 lb (2.0 kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-7/UGN	Yes	Mating	Friction	Mating	3.8 lb (1.7 kg)	D-ring back pad / Pull-free lanyard rings / Belt loops
P950-77/UGN	Yes	Mating	Friction	Tongue	5.6 lb (2.5 kg)	D-ring back pad / Pull-free lanyard rings / Belt loops Removable tool belt / 6" (152 mm) back pad
P950-78/UGN	Yes	Mating	Friction	Mating	5.5 lb (2.5 kg)	D-ring back pad / Pull-free lanyard rings / Belt loops Removable tool belt / 6" (152 mm) back pad

Limitless Possibilities. Ask the Expert.
Technical Service: 800.873.5242
www.honeywellsafety.com

Honeywell Safety Products USA, Inc.
855 S Mint St
Charlotte, NC 28202
www.honeywell.com

USA
Phone: 800.430.5490
Fax: 800.322.1330

⚠ This equipment should only be used after reading and understanding the manufacturer's instructions. Failure to follow instructions could result in serious injury or fatality.

Canada
Phone: 888.212.7233
Fax: 888.667.8477

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell