

Product Specifications

Item #KEV4316



D-ROC®
by Magid

**Magid® D-ROC® Para-Aramid Rough Nitrile Palm
Coated Glove – Cut Level 2**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose – Cut Resistant
Construction/Design	13-gauge, seamless machine knit shell
Composition	96% Para-Aramid 4% Lycra shell, rough Nitrile-palm coating
Color(s)	Yellow shell, black coating
Size(s)	6 - 12
Cuff/Finish	Color coded rubber band edge, (6) Blue; (7) White; (8) Green; (9) Brown; (10) Yellow; (11) Grey, (12) Black
Unit of Measure	Dozen
Packaging	1 dozen per inner pack, 12 inner packs per case

FEATURES & BENEFITS	
• Black, premium, rough nitrile palm coating provides channels away oils ensuring a tight grip, especially compared to plastic coating • Yellow, seamless para-aramid/Lycra blended machine knit shell provides the optimal benefits of para-aramid for strength and Lycra® for stretch and comfort • Para-aramid fiber is five times stronger than steel and offers exceptional cut and puncture resistance • Dark color palm coating hides the dirt, extending the life of the glove • NEAT Tested • EN 407 Contact Heat Level 1 • Knit wrist and not liquid proof	

APPLICATIONS	
Appliance industry, assembly, automotive, metal fabrication and metal stamping	

AVAILABLE STYLES							
Size	6	7	8	9	10	11	12
Part Number	KEV43166	KEV43167	KEV43168	KEV43169	KEV431610	KEV431611	KEV431612

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
European Standard: EN 407: Protection Against Thermal Risks (Heat and/or Fire)		
Test Method	Clause	EN Level
EN 407 Contact Heat	6.4	Pass/Level 1
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
It is recommended that the gloves be machine washed. The water temperature cannot exceed 40°C/104°F. Do not use bleach. The gloves can be air dried or tumbled dry low temp.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades. Products that contain natural rubber latex may cause allergic reactions in some individuals.		

Originator	Adam Cohen	Date	10/05/2003		
Revised By	Kim Schultz	Date	1/07/2025	Revision #	6