

Product Specifications

Item #KEV4319



D-ROC®
by Magid

**Magid® D-ROC® KEV4319 Lightweight Para-Aramid
Foam Nitrile Palm Coated Glove – ANSI Cut Level A3**

PRODUCT DESCRIPTION	
Product Classification	Special Purpose – Cut Resistant
Construction/Design	13-gauge, seamless machine knit shell
Composition	96% Para-Aramid, 4% Lycra shell, Foam Nitrile-palm coating
Color(s)	Yellow shell, grey coating
Size(s)	6 - 11
Cuff/Finish	Color coded rubber band edge, (6) Blue; (7) White; (8) Green; (9) Brown; (10) Yellow; (11) Grey
Unit of Measure	Dozen
Packaging	1 dozen per inner pack, 12 inner packs per case

FEATURES & BENEFITS	
• Yellow, seamless para-aramid/Lycra blended machine knit shell provides the optimal benefits of para-aramid for strength and Lycra® for stretch and comfort • Soft, grey foam nitrile palm coating channels away oils ensuring a tight grip, especially compared to plastic coating while still being form-fitting and comfortable • Para-aramid fiber is five times stronger than steel and offers exceptional cut and puncture resistance • ANSI Cut Level A3 Cut Resistance and ANSI Level 4 Abrasion Resistance • Knit wrist colored overedge with a rubber band finish reduces fraying and provides a visual aid in sizing • Can be laundered to increase wear time • PPG Tested • Not liquid proof	

APPLICATIONS	
Appliance industry, assembly, automotive, metal fabrication and metal stamping	

AVAILABLE STYLES						
Size	6	7	8	9	10	11
Part Number	KEV43196	KEV43197	KEV43198	KEV43199	KEV431910	KEV431911

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A3
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	4
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Machine wash gloves in water temperatures not exceeding 40°C/104°F. Do not use bleach. The gloves can be air dried or tumbled dry low temperature. Limit number of washes to five total.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades. Products that contain natural rubber latex may cause allergic reactions in some individuals.		

Originator	Joe Conidi	Date	10/03/12	
Revised By	Kim Schultz	Date	11/09/2023	Revision # 5