

# Product Specifications

Item #KEV4327



**Magid® K-ROC® Lightweight Para-Aramid  
Polyurethane Palm Coated Glove – ANSI Cut Level A2**

## PRODUCT DESCRIPTION

<b>Product Classification</b>	Special Purpose – Cut Resistant
<b>Construction/Design</b>	13-gauge, seamless machine knit shell
<b>Composition</b>	Para-aramid and nylon blended shell, polyurethane-palm coating
<b>Color(s)</b>	Yellow shell, grey coating
<b>Size(s)</b>	6 - 12
<b>Cuff/Finish</b>	Rubber band edge, (6) Blue; (7) White; (8) Green; (9) Brown; (10) Yellow; (11) Grey; (12) White
<b>Unit of Measure</b>	Dozen
<b>Packaging</b>	1 dozen per inner pack, 12 inner packs per case

## FEATURES & BENEFITS

- Para-aramid fiber is 5 times stronger than steel and offers exceptional cut resistance
- Lycra enables the glove to be stretchable, form fitting and comfortable
- Polyurethane coating provides excellent grip, abrasion resistance and dexterity for precise and delicate operations
- Color-coded overcast reduces fraying and acts as a visual aid for sizing
- NEAT Tested
- ANSI level A2 cut resistance and ANSI level 5 abrasion resistance

## APPLICATIONS

Appliance industry, assembly, automotive, metal fabrication and metal stamping

## AVAILABLE STYLES

Size	6	7	8	9	10	11	12
<b>Part Number</b>	KEV43276	KEV43277	KEV43278	KEV43279	KEV432710	KEV432711	KEV432712

## FUNCTIONAL PERFORMANCE

### US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	2
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	5
EN 388:2003 Puncture Resistance	6.4	4

### US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A2

## SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

<b>Critical Defects</b>	Holes/tears
<b>Major Defects</b>	Dimensional or weight nonconformance, discoloration, other fabric defects

## LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

## GENERAL INFORMATION

**CAUTION** – This product is cut resistant, not cut proof, or puncture resistant. Do not use near moving or serrated blades. Products that contain natural rubber latex may cause allergic reactions in some individuals.

<b>Originator</b>	Efi Vrshek	<b>Date</b>	08/06/13	
<b>Revised By</b>	Kim Schultz	<b>Date</b>	11/09/2023	<b>Revision #</b> 5

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD