

Product Specifications

Item #KEV8616



**Magid® K-ROC® Lightweight Para-Aramid & Lycra®
Rough Nitrile Palm Coated Glove – Cut Level 4**

PRODUCT DESCRIPTION						
Product Classification	Special Purpose Work Glove – Cut and Flame Resistant					
Construction/Design	13-gauge, seamless machine knit					
Composition	Para-aramid, steel wire and Lycra shell; rough nitrile palm coating					
Color(s)	Yellow shell; black palm coating					
Size(s)	7- 12					
Cuff/Finish	Color-coded overcast: white (7), green (8), brown (9), yellow (10), grey (11), black (12)					
Unit of Measure	Dozen					
Packaging	1 dozen per inner pack, 12 inner packs per case					
FEATURES & BENEFITS						
• Para-aramid fiber is 5 times stronger than steel, offering exceptional cut and flame resistance • Blended with Lycra for improved comfort and steel wire for increased cut resistance • Premium rough nitrile palm coating channels away oils ensuring a tight grip • Color-coded overcast acts as a visual aid for sizing and reduces fraying • PPG and NEAT Tested • Machine washable for longer service life • ANSI Level 4 Cut Resistance and ANSI Level 4 Abrasion Resistance						
APPLICATIONS						
Assembly, machining, automotive manufacturing, metal handling, glass handling, maintenance and construction						
AVAILABLE STYLES						
Size	7	8	9	10	11	12
Part Number	KEV86167	KEV86168	KEV86169	KEV861610	KEV861611	KEV861612

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	4
Abrasion Resistance	-	4
Puncture Resistance	6.4	3
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.		

Originator	Adam Cohen	Date	10/5/03	
Revised By	Olivia DeVries	Date	06/01/2022	Revision # 6

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.