

Product Specifications

Item #KEV8627



D-ROC®
by Magid

Magid® D-ROC® KEV8627 Lightweight Para-Aramid & Lycra® Polyurethane Palm Coated Glove – ANSI Cut Level 4

PRODUCT DESCRIPTION

Product Classification	Special Purpose Work Glove – Cut and Flame Resistant
Construction/Design	13-gauge, seamless machine knit shell
Composition	Para-aramid, Lycra and stainless-steel blended shell, polyurethane-palm coating
Color(s)	Yellow shell, grey coating
Size(s)	6-11
Cuff/Finish	Rubber band edge: (6) blue; (7) White; (8) Green; (9) Brown; (10) Yellow; (11) Grey
Unit of Measure	Dozen
Packaging	1 dozen per inner pack, 12 inner packs per case

FEATURES & BENEFITS

- Para-aramid fiber is 5 times stronger than steel, offering exceptional cut and flame resistance
- Lycra® enables the glove to be stretchable, form fitting and comfortable
- Stainless steel enhances cut protection
- Polyurethane coating provides excellent grip, abrasion resistance and dexterity for precise and delicate operations
- Color-coded overcast reduces fraying and acts as a visual aid for sizing
- PPG Tested
- ANSI level A4 cut resistance and ANSI level 3 abrasion resistance

APPLICATIONS

Appliance industry, assembly, automotive, metal fabrication and metal stamping

AVAILABLE STYLES

Size	6	7	8	9	10	11
Part Number	KEV86276	KEV86277	KEV86278	KEV86279	KEV862710	KEV862711

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A4
ASTM D3389 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	2,515	3
EN 388 Puncture Resistance	6.4	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades. Products that contain natural rubber latex may cause allergic reactions in some individuals.

Originator	Efi Vrshek	Date	8/6/13	
Revised By	Kim Schultz	Date	11/16/2023	Revision # 4

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD