

Duo-Mix 405

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Neoprene and natural latex
- **Length (cm)** 33
- **Thickness (mm)** 0.70
- **Wrist** Straight cuff
- **Colour/Color** Blue / Yellow
- **Interior finish** Flocked
- **Exterior finish** Embossed texture
- **Size / EAN** 6 7 8 9 10
- **Packaging** 1 pair/bag - 10 pairs/bag - 100 pairs/carton



PERFORMANCE RESULTS

Certification category 3

CE 0334



2120

Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Blade cut resistance
 └─ Abrasion resistance
 └─ Tear resistance
 └─ Puncture resistance



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**RADIOACTIVE
CONTAMINATION
EN 421**



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Burning behaviour
 └─ Contact heat resistance
 └─ Convective heat resistance
 └─ Radiant heat resistant
 └─ Resistance to small drops of molten metal
 └─ Resistance to large quantities of molten metal



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofuran
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Convective cold resistance
 └─ Contact cold resistance
 └─ Water permeability

For more details: www.mapa-pro.com

Duo-Mix 405

DESCRIPTION AND GENERAL PROPERTIES

- Tactile sensitivity, due to the gloves reduced thickness
- Comfort and perspiration absorption, due to the cotton flock-lining
- Good grip, due to the non-slip embossing

MAIN FIELDS OF USE

Automotive/mechanical industry

- Spray-painting

Other industries

- Industrial cleaning, maintenance

Aeronautics industry

- Work with composite materials (resins)

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service • MAPA PROFESSIONNEL (stc.mapaspontex@mapaspontex.fr) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with a solvent (alcohols, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth

Caution : using the gloves or submitting them to another cleaning or laundering process can alter their performance levels.

Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

Food contact US

FDA 21CFR 177.2600

LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/11/10/0469

- Issued by the notified body nr

0075

C.T.C. – 4 rue Hermann Frenkel - F- 69367 LYON Cedex 07

- Quality assurance certificat

0334 Asqual 14 rue des Reculettes -F-75013 PARIS

MAPA[®]
PROFESSIONNEL
www.mapa-pro.com