

Product Specifications

Item #PF540



Magid® D-ROC® Lightweight Polyurethane Palm Coated Glove – Cut Level 2

PRODUCT DESCRIPTION					
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated				
Construction/Design	13-gauge, seamless machine knit				
Composition	Hyperon™ fiber blended shell; polyurethane palm coating				
Color(s)	White shell; white palm coating				
Size(s)	6 – 10				
Cuff/Finish	Color-coded elasticized overcast: white (6), green (7), brown (8), yellow (9), grey (10)				
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)				
Packaging	12 pairs per inner pack, 12 inner packs per case (144 pairs per case)				
FEATURES & BENEFITS					
• Durable 13 gauge Hyperon™ shell delivers breathability, comfort, and 360° cut protection • Polyurethane palm coating channels away oils and ensures a secure grip • Color-coded overcast acts as a visual aid for sizing • Elasticized finish on cuff reduces fraying • Machine washable for longer service life • ANSI Level 2 Cut Resistance and ANSI Level 2 Abrasion Resistance					
APPLICATIONS					
Assembly, machining, automotive manufacturing, metal handling, maintenance and construction					
AVAILABLE STYLES					
Size	6	7	8	9	10
Part Number	PF5406	PF5407	PF5408	PF5409	PF54010

FUNCTIONAL PERFORMANCE		
US Standard: ANSI/ISEA 105-2011 American National Standard for Hand Protection Selection Criteria		
Test Method	Clause	ANSI Level
Cut Resistance	-	2
Abrasion Resistance	-	2
Puncture Resistance	-	3
European Standard: EN 388:2003 Protective Gloves Against Mechanical Risks		
Test Method	Clause	EN Level
Blade Resistance	6.2	3
SERVICE LIFE		
The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.		
Critical Defects	Holes/tears	
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects	
LAUNDERING GUIDELINES		
Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.		
GENERAL INFORMATION		
CAUTION – This product is cut resistant, not cut proof or puncture resistant. Do not use near moving or serrated blades.		

Originator	Debbie Richter	Date	08/12/2008	
Revised By	Joe Conidi	Date	05/22/2015	Revision # 7

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

