

Product Specifications

Style #PPD520



D-ROC®
by Magid

Magid® High-Visibility NitriX® Coated Padded Palm Work Glove – Cut Level A5

For jobs that involve the use of power tools, the Magid® PPD520 Hi-Viz Padded Palm Coated work glove dampens impact to the palm allowing for better control and productivity. PPD520 offers 360° cut protection while also protecting against puncture and visibility hazards to deliver the best overall value.

PRODUCT DESCRIPTION

Product Classification	Anti-Vibration Work Glove – Cut Resistant, Coated
Construction/Design	15-gauge, seamless machine knit
Composition	DuraBlend™ shell; NitriX® Grip palm coating
Color(s)	Hi-viz yellow shell; black palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 12 inner packs per case

FEATURES & BENEFITS

- 360° ANSI Cut Level A5 protection, ANSI Level 3 Abrasion Resistance and ANSI Level 3 Puncture Resistance
- Padded palm dampens impact allowing for better control
- NitriX® Grip technology sandy nitrile palm coating ensures a secure grip in wet, dry or oily applications
- High-visibility color enhances worker protection and ensures worker compliance
- Form-fitting DuraBlend shell delivers breathability, comfort and dependable cut protection
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Latex Free

APPLICATIONS

Assembly, manufacturing, maintenance, material handling and any work with power tools.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Part Number	PPD5205	PPD5206	PPD5207	PPD5208	PPD5209	PPD52010	PPD52011	PPD52012

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F-1790-97 Cut Resistant	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	3
EN 388:2003 Puncture Resistance	6.4	3

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect as defined below is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Sarah Anderson	Date	7/27/2015	
Revised By	Scott Daigle	Date	5/2/2019	Revision #

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD