

VENTURE II®

THE ORIGINAL DUAL LENS WRAP AROUND SAFETY GLASS



PART

SB1810S***

SB1810ST***

SB1820S***

SB1820ST***

SB1830S***

SB1835S***

SB1840S***

SB1860S***

LENS

Clear

Clear (Anti-Fog)

Gray

Gray (Anti-Fog)

Amber

Sun Block Bronze

Orange

Infinity Blue

PART

SB1870S***

SB1875S***

SB1880S***

SB1880ST***

SB1890S***

SB1850SF***

SB1860SF***

LENS

Silver Mirror

Blue Mirror

Indoor/Outdoor Mirror

Indoor/Outdoor Mirror (Anti-Fog)

Gold Mirror

5.0 IR

3.0 IR

- Temples adjust to four different lengths.
- Lenses coated for superior scratch resistance.
- Nose buds secure the glass and prevent slipping while providing a pillow soft fit.
- 9.75 base curved lens provides full side protection without distracting seams or traditional type side shield, provides 99.9% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 10.5mm

Lens Base: 9.75 Curve

Lens Size Diagonal: 56mm

Lens Size Vertical: 45mm

Lens Thickness: 2.2mm

Overall Length (Lens-Tip): 150-163mm

Overall Width (Hinge-Hinge): 142mm

PD: 68mm

Weight: 27gm

PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

VENTURE II®

THE ORIGINAL DUAL LENS WRAP AROUND SAFETY GLASS

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	High curve dual lens, side shield integrated to lens
Frame	Nylon 6.6	Lens removable from frame matte finish
Side Shield	Polycarbonate	Integral to lens
Nose Piece	V bridge - PC	V bridge holds pad in place
	Soft pad - TPR	TPR = thermoplastic elastomer
Sleeve (on temple)	Nylon 6.6	Adjustable to 4 length positions
Temple	Nylon 6.6	Adjustable
Temple Tip	N/A	N/A
Hinge	PC/Nylon	3 barrel type, integral to frame/sleeve
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB1810S	 Clear	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1810ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1820S	 Gray	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1820ST	 Gray (Anti-Fog)	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1830S	 Amber	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1835S	 Sun Block Bronze	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1840S	 Orange	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1860S	 Infinity Blue	P Z87 + U6 L1.3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1870S	 Silver Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1875S	 Blue Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1880S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1880ST	 Indoor/Outdoor Mirror (Anti-Fog)	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1890S	 Gold Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1850SF	 5.0 IR	P Z87 + W3 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
SB1860SF	 3.0 IR	P Z87 + W3 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

W: Welding Filter

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA standard for protection devices