

INSULATING RUBBER GLOVES



SALISBURY INSULATING RUBBER GLOVES are available in sizes 7 through 12, including some half sizes. Proper fit is important to minimize chafing and fatigue. To determine glove size, measure the circumference around the palm. Allow for additional room if fabric glove liners are to be worn, especially with thermal liners.

Class 00 gloves are available in red and black, Type I Natural Rubber or blue and contrasting blue/orange Type II Salcor® ozone resistant rubber. Class 0 gloves are available in red, yellow and black, Type I Natural Rubber or blue Type II Salcor® ozone resistant rubber. The contrast between the thin outer orange color against the inner blue color makes inspecting for cuts and tears easier when the glove is inflated or stretched.

Class 2 gloves are available in Type I Natural Rubber only. All insulating rubber gloves are extremely flexible and make working with small parts easy. The gloves meet or exceed ASTM D120 and IEC EN60903 Standards.

INSULATED RUBBER GLOVES

CLASS	LENGTH	COLOR	SIZE (choose one below)
E 00	11 or 14	R, BL, B, Y or BLO	7, 8, 8H, 9, 9H 10, 10H, 11, 12
E 0	11 or 14	R, BL, B, Y or BLO	
E 1	14,16 or 18	B, YB or RB	
E 2	14,16 or 18	B, YB or RB	

Class 3 and Class 4 Available.

EXAMPLE: E011R10 is a Class 0 11" red glove size 10.

Type I Natural Rubber available in: R=Red, Y=Yellow, B=Black, RB=Red in, Black out, YB=Yellow in, Black out.

Type II Salcor® Rubber available in: BL=Blue, BLO=Blue in, Orange out.



TEN-FOUR® GLOVE DUST is a cooling, frictionless powder that absorbs moisture and perspiration when wearing rubber gloves. The 5-oz. bottle easily fits in a pocket or glove bag. The 4-quart bulk package is used in test labs as a dusting powder.

TEN-FOUR® GLOVE DUST

CAT. NO.	DESCRIPTION	WEIGHT lbs. (kgs)
10-4	12, 5 oz. Squeeze bottles	5.5 (12)
10-4-4QT	4 qt. Bulk, single	8 (19)

INSULATING RUBBER GLOVES MAXIMUM USAGE

CLASS	PROOF TEST VOLTAGE AC / DC	MAX. USE VOLTAGE AC / DC
00	2500 / 10,000	500 / 750
0	5,000 / 20,000	1,000 / 1,500
1	10,000 / 40,000	7,500 / 11,250
2	20,000 / 50,000	17,000 / 25,500
3	30,000 / 60,000	26,500 / 39,750
4	40,000 / 70,000	36,000 / 54,000



MEASURE THE CIRCUMFERENCE AROUND THE PALM TO DETERMINE THE SIZE OF THE GLOVE.

Contact a Salisbury customer service representative for extensive arc flash testing data performed on the insulating rubber gloves.

LEATHER PROTECTORS AND GLOVE LINERS

LEATHER PROTECTOR GLOVES should always be worn over insulating rubber gloves to provide the needed mechanical protection against cuts, abrasions and punctures. The ILP Series is manufactured from top grain cowhide or goatskin. Cowhide cuffs are tough leather on palm side and orange vinyl on the back, while the goatskin cuffs are green leather on palm side and orange vinyl on back. The ILP10 gloves do not have a cuff. Full complement of styles from low-volt through 16" contour cuff. Leather protector gloves come in dual sizes 7/7.5 through 11/11.5 and 12. Protectors for Class 00 and 0 are available with non-metallic buckle and pull strap or elastic wrist.

It is the responsibility of the purchaser to specify the overall length of the protector gloves. The Clearance Table shows the minimum distance which shall be allowed between the top of the protector glove cuff and the top end of the bead of the rubber glove per ASTM F496 Specifications.

WARNING: Do not use leather protectors alone for protection against electric shock. Serious injury or death will result. Always use proper insulating rubber gloves.

Proper care of leather protectors is essential to user safety. Inspect the leather protectors when inspecting rubber gloves. Metal particles, imbedded wire, abrasive materials or any substance that could physically damage the rubber gloves must be removed from the protector before use.

LINER GLOVES reduce the discomfort of wearing Insulating Rubber Gloves in all seasons. For year round use, liners provide warmth in cold weather while they absorb perspiration in the warm months. Many styles and fabrics are available with either a open or knit wrist.

The knit wrist style grips the wrist rather than allowing the cuff to roll down and bunch at the palm. All Liner Gloves are for year round use with Insulating Rubber Gloves and Mittens. All liners are made from stretch fabric that can fit any hand size.

The L Series has a tough outer cotton fabric while the inner lining is soft and comfortable. The LMKC Series is light, airy and allows ease of movement. The LMKW Series is made from a fabric that moves easily yet gives a substantial layer of lining.

LINER GLOVES

CAT. NO.	DESCRIPTION	WRIST Style	LENGTH in. (mm)	WEIGHT EA. lbs. (kgs)
L10JK	Jersey style, light weight, seams out	Knit	10 (254)	.14 (.06)
L12J	Jersey style, light weight, seams out	Open	12 (305)	.14 (.06)
L10MKW	Machine knit, cotton/wool blend	Knit	10 (254)	.14 (.06)

One size fits all.



LEATHER PROTECTOR CLEARANCE TABLE

GLOVE CLASS	MIN. DISTANCE BETWEEN TOP OF PROTECTORS AND RUBBER GLOVES	
	in.	mm
00, 0	1/2	13
2	2	51

LEATHER PROTECTORS

CAT. NO.		OAL LENGTH in. (mm)	WEIGHT lbs. (kgs)
Cowhide	Goatskin		
ILP3S	ILPG3S	12 (305)	1 (.5)
ILP5S	ILPG5S	14 (356)	1.2 (.5)
ILP7C	ILPG7C	16 (406)	1.5 (.7)
ILP10	ILPG10	10 (254)	.7 (.32)
ILP10A	ILPG10A	10 (254)	.7 (.32)

S=straight cuff, C=contour cuff, A=w/ pull strap.

Sizes: 7/7.5, 8/8.5, 9/9.5, 10/10.5, 11/11.5, 12



INSULATING GLOVES AND PROTECTORS KITS

SHOCK PROTECTION



MEASURE THE CIRCUMFERENCE AROUND THE PALM TO DETERMINE THE SIZE OF THE GLOVE.

NOTE: If you require test date stamping, please specify when ordering.

GLOVE KITS - Salisbury's insulating rubber gloves are necessary for every electrical worker's complete safety. Salisbury's leather protectors provide needed protection from cuts, abrasions and punctures. To keep these safety items in top condition, proper storage is very important.

Proper storage extends the service life of gloves. Folds and creases strain natural rubber and cause it to cut from ozone prematurely. Storing rubber gloves in the right size bag and never forcing more than one pair into each bag, equipment will lie flat and last longer.

PRODUCT NUMBERING CHART FOR GLOVE KITS

CLASS	LENGTH (inches)	COLOR	GLOVE SIZE (choose one below)
GK 00	11 or 14	B, BL, Y, R	7, 8, 8H, 9, 9H
GK 0	11 or 14	B, BL, Y, R	10, 10H, 11, 12
GK 2	14, 16, or 18	B, RB	
Example: GK011BL9	11	BL	9

GK011BL9 is a glove kit with a Blue Class 0 glove 11" long size 9. The appropriate glove bag and leather protectors will be included.

Type I Natural Rubber available in: R=Red, Y=Yellow, B=Black

RB=Red in, Black out.

Type II Salcor® Rubber available in: BL=Blue



PRO-WEAR® ARC FLASH GLOVES

12 - 100 CAL/CM²

SALISBURY PRO-WEAR® ARC FLASH GLOVES are available in ATPV ratings of 12 to 100 cal/cm²*. These gloves are sewn with Nomex® thread. All gloves are made with arc rated material.

All Arc Flash Gloves are 14" long and designed in a cleft cut style. One size fits most.

CAT. NO.	DESCRIPTION
AFG11	12 cal/cm ² , Navy blue,
AFG20	20 cal/cm ² , Navy blue
AFG31	31 cal/cm ² , Royal blue
AFG40	40 cal/cm ² , Gray
AFG55*	55 cal/cm ² , Gray
AFG100*	100 cal/cm ² , khaki



CAUTION: ARC FLASH GLOVES DO NOT PROVIDE ELECTRICAL PROTECTION. DO NOT USE WHEN INSULATING RUBBER GLOVES ARE REQUIRED.

***IMPORTANT:** NFPA 70E DOES NOT HAVE A HAZARD RISK CATEGORY ABOVE 40 CAL/CM². WORKING ON LEVELS ABOVE 40 CAL/CM² SHOULD BE AVOIDED BECAUSE OF THE BLAST HAZARDS CAUSED BY ARC FLASH.