

Product Specifications

Item #TRX441



T-REX[®]
by Magid

**Magid[®] T-REX[®] Flex Series[®] Lightweight NitriX[®]
Grip Technology Palm Coated Impact Glove –
ANSI Cut A5**

PRODUCT DESCRIPTION

Product Classification	Impact Glove – Cut Resistant, Coated
Construction/Design	Seamless machine knit shell, impact protection on back of hand, fingers and fingertips
Composition	Hyperon [®] shell; NitriX [®] Grip Technology sandy nitrile palm coating; thermoplastic rubber (TPR) impact pads on the back of the hand and fingers
Color(s)	Salt & pepper shell; black palm coating; hi-vis green/yellow TPR pads
Size(s)	XS – 4XL
Cuff/Finish	Knit wrist cuff with hook and loop closure and color-coded overcast
Unit of Measure	Pair
Packaging	12 pairs per inner pack; 72 pairs per case

FEATURES & BENEFITS

- 13-gauge Hyperon[®] shell delivers lightweight comfort and dependable cut protection
- NitriX[®] Grip Technology palm coating delivers rock-solid grip in oily applications, enhanced abrasion resistance and increases wear life
- M-Force Defense System[®] back-of-hand protection extends all the way to the fingertips and between thumb and index finger to deflect and absorb impacts
- Nitrile reinforced thumb saddle enhances durability at a critical wear point
- Hook & loop wrist closure ensures a secure fit
- Color-coded overcast acts as a visual aid for sizing and helps prevent fraying
- Machine washable for longer service life
- ANSI Level A5 Cut Resistance, ANSI Level 5 Abrasion Resistance, and ANSI Level 4 Puncture Resistance
- ANSI/ISEA 138 Impact Level 2 (Level 2 protection on knuckles and Level 2 protection on fingers)

APPLICATIONS

Oil & gas rigging, fracking, refining, manufacturing, heavy construction, light construction, demolition, agriculture, emergency response, military, extraction, mining, steelwork, ironwork, tool work, maintenance, supervisory, towing, automotive, metal stamping, glass handling.

AVAILABLE STYLES

Size	XS	S	M	L	XL	2XL	3XL	4XL
Item #	TRX441XS	TRX441S	TRX441M	TRX441L	TRX441XL	TRX441XXL	TRX441XXXL	TRX441XXXXL

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992 Cut Resistance	-	A5
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)	-	5
EN 388:2003 Puncture Resistance (other than hypodermic needle)	6.4	4

US Standard: ANSI/ISEA 138-2019 American National Standard for Performance and Classification for Impact-Resistant Gloves

Test Method	Clause	ANSI Level
ISEA 138:201x Impact Protection (Overall)	-	2
ISEA 138:201x Impact Protection (Knuckles)	-	2
ISEA 138:201x Impact Protection (Fingers and Thumb)	-	2

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Adrianna Carrera	Date	4/30/2019	
Revised By	Kim Schultz	Date	8/25/2023	Revision # 9

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD