Product Specifications

Item #TRX442





Magid[®] T-REX[®] TRX442 Flex Series[®] Lean Lightweight Polyurethane Palm Coated Low-Profile Impact Glove – Cut Level A4

PRODUCT DESCRIPTION							
Product Classification Impact Glove – Cut Resistant, Coated							
Construction/Design	13-gauge, seamless machine knit shell; low profile impact protection on back of hand, fingers and fingertips; flat reinforced thumb saddle						
Composition	Hyperon [®] fiber blended shell; polyurethane palm coating; thermoplastic rubber (TPR) impact pads on the back of the hand and fingers; Para-aramid reinforced thumb saddle						
Color(s)	Salt & pepper shell; grey palm coating; hi-viz yellow, orange, and black TPR pads; black thumb saddle						
Size(s)	XS – 4XL						
Cuff/Finish	Knit wrist cuff with color-coded overcast						
Unit of Measure	Pair						
Packaging	12 pairs per inner pack; 72 pairs per case						

- **FEATURES & BENEFITS**
- Durable13-gauge Hyperon[®] blended shell delivers breathability, comfort and 360° cut protection
- Polyurethane palm coating maintains dexterity while delivering an excellent grip
- Low profile M-Force Defense System[™] back-of-hand protection is 60% thinner and 40% lighter than standard impact protection to deflect and absorb impacts while maintaining flexibility to prevent hand fatigue
- 30% lighter than a standard impact glove, making it perfect for light-duty jobs
- Para-aramid reinforced thumb saddle enhances durability at a critical wear point
- Color-coded overcast acts as a visual aid for sizing and reduces fraying
- Machine washable for longer service life
- ANSI Level A4 Cut Resistance, ANSI Level 5 Abrasion Resistance, and ANSI Level 5 Puncture Resistance
- ANSI/ISEA 138 Impact Level 1 (Level 1 protection on knuckles and Level 1 protection on fingers)



APPLICATIONS

Oil & gas wireline, I&E, light construction, tool work, maintenance, supervisory, assembly, automotive, sheet metal work, glass
handling.

AVAILABLE STYLES										
Size	XS	S	S M L XL 2XL		3XL	4XL				
Item #	TRX442XS	TRX442S	TRX442M	TRX442L	TRX442XL	TRX442XXL	TRX442XXXL	TRX442XXXXL		
			FUNCT	ONAL PERFOR	MANCE					
	US Standard:	ANSI/ISEA 105	-2016 America	n National Star	ndard for Har	d Protection Se	lection Criteria	1		
Test Method						Clause	ANSI Level			
ASTM F2992 Cut Resistance						-	A4			
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000-gram load)					oad)	-	5			
EN 388:2003 Puncture Resistance (other than hypodermic needle)						6.4	6.4 5			
US Standa	rd: ANSI/ISEA 13	8-2019 Amerio	an National St	andard for Per	formance an	d Classification f	or Impact-Res	istant Gloves		
Test Metho	d					Clause	AN	SI Level		
ISEA 138:201x Impact Protection (Overall)						-	1			
ISEA 138:201x Impact Protection (Knuckles)						-	- 1			
ISEA 138:201x Impact Protection (Fingers and Thumb)						- 1		1		
				SERVICE LIFE						
	life of this produ mediately once a		-			administered. T	his product sh	ould be		
Critical Defects Holes/tears										
Major Defects Dimensional or weight nonconformance, discoloration, other fabric defects										
			LAUN	DERING GUIDE	LINES					
	nachine washab with a low temp		-			perature is 35°-4 nlight.	0°C/95°-104°F.	Air dry or		
			GENE	RAL INFORMA	TION					
CAUTION -	This product is c	ut and punctur	e resistant, not	cut and punct	ure proof. Do	not use near mo	oving or serrate	ed blades.		

Originator	Scott Daigle	Date	11/14/2018		
Revised By	Kim Schultz	Date	7/13/2023	Revision #	4

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

©Magid Glove & Safety Mfg. Co. LLC. Magid[®] is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

